REVIEW OF RESEARCH
ISSN: 2249-894X
IMPACT FACTOR : 5.7631(UIF)
VOLUME - 8 | ISSUE - 11 | AUGUST - 2019

IMPLEMENTATION OF ARTIFICIAL INTELLIGENCE IN DEVELOPING A COST-EFFECTIVE SOLAR ENERGY SYSTEM

Dr. Sayyad Razak Nizam
Department of Computer Science, Ahmednagar College.

ABSTRACT:

Solar energy is one of the most promising renewable energy sources for meeting the growing global demand for electricity. However, conventional solar photovoltaic (PV) systems face several challenges, including variable power generation, reduced efficiency under changing environmental conditions, unexpected component failures, inefficient energy utilization, and maintenance costs. Artificial Intelligence (AI) offers opportunities to address these challenges by enabling intelligent monitoring, predictive maintenance, solar power forecasting, maximum power point tracking, and optimized energy management.



This research proposes an AI-assisted, cost-effective solar energy system that integrates low-cost sensors, a microcontroller, machine learning algorithms, and an intelligent energy management framework. The proposed system collects environmental and electrical parameters, including solar irradiance, temperature, voltage, current, and energy consumption. These parameters are analyzed to estimate solar power generation, detect abnormal operating conditions, and optimize the utilization of generated electricity.

To maintain affordability, the proposed architecture uses readily available hardware and lightweight machine learning models that can operate on low-cost computing platforms. The system is intended to be suitable for residential rooftops, educational institutions, small commercial establishments, and rural electrification applications.

The research establishes a methodology for evaluating system performance in terms of energy generation, prediction accuracy, fault detection, operational cost, and overall economic feasibility. Rather than assuming that AI automatically improves efficiency, the study proposes a comparative evaluation between a conventional solar system and an AI-assisted system. The framework aims to identify whether the additional investment in AI hardware and software can be justified by improved energy utilization, reduced maintenance expenditure, and lower lifecycle costs.

KEYWORDS: *Artificial Intelligence, Solar Photovoltaic System, Machine Learning, Maximum Power Point Tracking, Predictive Maintenance, Energy Optimization, Internet of Things, Cost-Effective Renewable Energy.*

1.INTRODUCTION:

The increasing demand for electricity and the environmental impacts associated with conventional energy generation have encouraged the adoption of renewable energy technologies. Among these technologies, solar photovoltaic systems have become an important option because they can convert sunlight directly into electrical energy and can be deployed at different scales.

Despite their advantages, solar PV systems are affected by variations in solar irradiance, ambient temperature, partial shading, dust accumulation, component degradation, and electrical faults. These factors can reduce energy

production and increase maintenance requirements.

Conventional solar installations commonly use predefined control strategies to regulate energy conversion. Although these methods are comparatively inexpensive and reliable, they may not respond optimally to all operating conditions.

Artificial Intelligence can improve the decision-making capabilities of solar installations by learning from historical and real-time data. Machine learning models can predict energy generation, identify unusual operating conditions, estimate maintenance requirements, and support intelligent decisions about when to store, consume, or export electricity.

Recent research has investigated AI applications in photovoltaic system design, power forecasting, fault diagnosis, and maximum power point tracking. Reviews published in 2023 and 2024 describe the development of intelligent control strategies and the potential advantages of AI-based photovoltaic monitoring and optimization [1], [2].

However, sophisticated AI systems may introduce additional costs through sensors, computing hardware, communication infrastructure, software development, and maintenance. Therefore, a practical solution must balance performance improvements against implementation expenses.

This research focuses on developing an affordable AI-assisted solar energy system using low-cost hardware and computationally efficient algorithms.

1.1 Problem Statement

Conventional solar PV systems can experience energy losses and higher operating costs because of changing environmental conditions, undetected faults, suboptimal energy management, and maintenance performed without sufficient information about component condition.

Although AI techniques can address these issues, their implementation may be expensive or unnecessarily complex for small installations.

The central research problem is therefore:

How can AI techniques be integrated into a solar PV system to improve energy utilization, operational reliability, and maintenance efficiency without significantly increasing the total cost of the installation?

1.2 Aim of the Research

The primary aim is to design and evaluate a cost-effective AI-assisted solar energy system that improves monitoring, forecasting, fault identification, and energy management.

1.3 Research Objectives

The specific objectives are:

1. To develop an affordable architecture combining solar PV hardware, environmental sensors, and AI-based monitoring.
2. To implement a machine learning model for short-term solar power generation forecasting.
3. To investigate intelligent methods for identifying abnormal electrical and environmental conditions.
4. To evaluate the potential application of AI-assisted maximum power point tracking.
5. To optimize the use of generated electricity according to demand and battery state of charge.
6. To compare the performance and lifecycle costs of conventional and AI-assisted solar systems.
7. To determine whether the benefits of AI justify its additional implementation and maintenance costs.

2. LITERATURE REVIEW

2.1 Artificial Intelligence in Solar Energy

AI includes computational methods that analyze data, identify patterns, and support decisions. Machine learning is particularly relevant to solar energy because PV performance depends on several interacting variables, many of which change over time.

Common techniques include:

- Artificial Neural Networks (ANN)
- Random Forest
- Support Vector Regression (SVR)
- Decision Trees
- Long Short-Term Memory Networks (LSTM)
- Fuzzy Logic
- Reinforcement Learning

The appropriate method depends on the application, available data, computing resources, and required response time.

For a small rooftop installation, a Random Forest model or a lightweight regression model may be more economical than a large deep-learning network.

2.2 AI-Based Solar Power Forecasting

Solar generation varies with irradiance, temperature, cloud cover, and other environmental factors. Accurate forecasts can help households and businesses schedule energy consumption and battery charging.

Machine learning models can use historical power generation and weather measurements to estimate future output.

Possible input variables include:

- Solar irradiance
- Ambient temperature
- PV module temperature
- Relative humidity
- Historical solar power generation
- Time of day
- Day of the year
- Weather conditions, when available

The predicted power output can be used by an energy management controller to determine whether stored energy should be reserved for later consumption or whether flexible electrical loads should operate immediately.

A 2026 scoping review of AI-based solar forecasting identifies forecasting accuracy, data quality, uncertainty estimation, and transferability between locations as important considerations when deploying these models [3].

2.3 AI-Based Maximum Power Point Tracking

Maximum Power Point Tracking (MPPT) is used to operate a PV array near the voltage and current combination that produces its maximum available power.

Traditional methods include Perturb and Observe (P&O) and Incremental Conductance.

These methods are widely used because they are comparatively simple and economical. However, rapid environmental changes and partial shading can complicate the tracking process.

AI-assisted techniques, including neural networks and fuzzy logic controllers, can estimate suitable operating conditions and adapt control decisions to changing environmental conditions.

Yap, Sarimuthu, and Lim reviewed AI-based MPPT techniques and discussed their potential advantages, implementation challenges, and computational costs [4].

For a cost-effective system, the proposed research recommends retaining a conventional MPPT controller when it offers satisfactory performance. AI should be introduced only when measurable improvements justify the additional expense.

2.4 Predictive Maintenance and Fault Detection

Solar installations can develop problems such as:

- Dust accumulation and shading
- Abnormal module temperature
- Loose or damaged electrical connections
- Unexpected reductions in power generation
- Sensor malfunction
- Inverter faults
- Battery degradation

Traditional maintenance may depend on scheduled inspections or alarms based on fixed thresholds.

An AI-assisted monitoring system can compare actual performance with expected performance under similar environmental conditions. Large or persistent deviations can trigger an alert for further inspection.

For example, if a PV array produces substantially less power than expected under comparable irradiance and temperature conditions, the system can flag a possible problem.

However, reduced output does not automatically prove that a panel is defective. Cloud movement, sensor errors, shading, inverter limitations, and other factors must also be considered.

AI-based fault detection should therefore support, rather than replace, appropriate electrical testing and professional maintenance.

2.5 Intelligent Energy Management

A solar installation may supply electricity directly to loads, charge a battery, or export surplus electricity to the grid.

The best choice depends on expected generation, electricity demand, battery condition, tariff structure, and grid-export arrangements.

AI-based forecasting can support decisions about energy allocation.

For example, when high solar generation is predicted, flexible loads such as water pumping may be scheduled during the daytime. When lower generation is expected, battery charging and electricity consumption can be planned accordingly.

The economic benefit depends on the installation's actual operating conditions. Grid-connected systems with limited export compensation may have different optimization priorities from off-grid systems.

3. PROPOSED SYSTEM ARCHITECTURE

3.1 Overview

The proposed system integrates a solar PV array, a charge controller or inverter, environmental sensors, electrical measurement devices, a processing unit, and an AI-based decision-support system.

The design is modular so that a basic installation can operate without expensive computing hardware. Additional functions can be introduced when they offer sufficient practical value.

The main components are:

1. Solar PV panels
2. Voltage and current sensors
3. Temperature sensor
4. Irradiance sensor, where economically feasible
5. Microcontroller or low-cost computing device
6. Conventional MPPT charge controller or compatible inverter
7. Battery and battery management system, where applicable
8. AI forecasting and anomaly-detection software
9. User interface for monitoring and alerts


10. Energy management controller

3.2 System Workflow

The system operates according to the following sequence:

Step 1: Data acquisition
Sensors collect electrical measurements, environmental parameters, and energy consumption data.
Step 2: Data preprocessing
The processing unit checks missing values, removes invalid measurements, identifies sensor errors, and prepares the data for analysis.
Step 3: Solar generation forecasting
A trained machine learning model estimates the expected PV output over a selected forecasting horizon.
Step 4: Performance monitoring
The system compares measured power with expected power to identify unusual deviations.
Step 5: Fault alerts
If a deviation exceeds a defined threshold for a sufficient period, the system generates an alert for investigation.
Step 6: Energy management
The controller uses predicted generation, load demand, and battery state of charge to support charging and consumption decisions.
Step 7: Performance evaluation
The system records energy generation, forecast errors, fault alerts, electricity costs, and maintenance events.

3.3 Proposed Block Diagram



The conventional inverter and its electrical protection systems remain responsible for safe power conversion and protection. The AI layer provides supplementary monitoring and optimization functions.

AI commands must not bypass inverter protections, battery management systems, electrical isolation requirements, or manufacturer-specified operating limits.

4. RESEARCH METHODOLOGY

4.1 Research Design

The study adopts a design-and-evaluation approach. The proposed system will be developed and compared with a conventional solar installation or a corresponding baseline simulation.

The methodology consists of five phases:

1. System design and hardware selection
2. Data collection and preprocessing
3. AI model development
4. Performance comparison
5. Economic feasibility analysis

The proposed methodology can be implemented through MATLAB/Simulink, Python, or a hardware prototype.

4.2 Hardware Requirements

A prototype may use the following components:

Component	Purpose
Solar PV module or existing solar installation	Electricity generation
Voltage and current sensors	Measurement of electrical performance
Temperature sensor	Monitoring of ambient or module temperature
Irradiance sensor	Measurement of available solar radiation
ESP32 or similar microcontroller	Sensor acquisition and communication
Raspberry Pi or computer, if required	Local model training or inference
Compatible inverter or MPPT controller	Power conversion and PV operating-point control
Battery and compatible BMS, if required	Energy storage and protection
Data logging software	Recording and analysis
Dashboard	Displaying measurements, forecasts, and alerts

A Raspberry Pi or dedicated computer is not essential if the selected model can run on an existing computer or a capable microcontroller.

For cost control, existing inverter telemetry and publicly available weather data may be used where appropriate and reliable. Sensor selection should be based on the accuracy needed for the intended application.

4.3 Data Collection

The proposed model uses historical and real-time measurements.

A suitable dataset should contain:

- Timestamp
- PV voltage
- PV current
- PV power
- Solar irradiance
- Ambient temperature
- Module temperature, if available
- Energy consumption
- Battery state of charge, if applicable

- Weather information, if available
- Maintenance events and known faults

The data should represent different operating conditions, including clear skies, cloudy periods, high temperatures, and variations in electricity demand.

For a preliminary prototype, measurements may be recorded at regular intervals, such as every five minutes. The sampling frequency should be adjusted according to the application and sensor capabilities.

A longer dataset is preferable for capturing seasonal variation.

4.4 Data Preprocessing

The collected data should be checked for accuracy before model training.

The preprocessing procedure includes:

1. Removing duplicate timestamps.
2. Identifying missing or invalid sensor readings.
3. Checking measurements against physically plausible operating ranges.
4. Synchronizing environmental and electrical measurements.
5. Creating time-based features.
6. Separating training, validation, and test periods chronologically.

Randomly distributing adjacent time-series observations across training and testing sets may lead to overly optimistic performance estimates. A chronological split is therefore recommended.

5. PERFORMANCE EVALUATION

The proposed framework should be evaluated using technical and economic indicators.

5.1 Forecasting Accuracy

Mean Absolute Error (MAE):

[
MAE=\frac{1}{N}\sum_{i=1}^{N}|P_i-\hat{P}_i|
]

Root Mean Square Error (RMSE):

[
RMSE=\sqrt{\frac{1}{N}\sum_{i=1}^{N}(P_i-\hat{P}_i)^2}
]

Where:

- P_i = measured PV power
- \hat{P}_i = predicted PV power
- N = number of observations

Lower MAE and RMSE values indicate more accurate forecasts on the evaluated dataset.

5.2 Energy Generation

Total energy generation over the observation period is:

[
E_{\text{PV}}=\sum_{i=1}^{N}P_i\Delta t
]

Where power is measured in kilowatts and the interval \Delta t is measured in hours, the result is in kilowatt-hours.

Energy generation should be compared under equivalent environmental conditions or evaluated using a suitable normalized baseline.

5.3 Fault Detection

Fault-detection performance can be evaluated using:

- Precision
- Recall
- F1-score
- False-alarm rate
- Detection delay

The study should distinguish between known faults and simulated anomalies. Performance on artificially generated anomalies does not necessarily establish performance on real equipment failures.

6. ILLUSTRATIVE COST ANALYSIS

To investigate affordability, a small rooftop installation can be used as an example.

The following table provides **illustrative planning ranges in Indian rupees**, not verified current quotations. Actual costs depend on system capacity, existing equipment, component quality, installation location, and whether the installation is grid-connected or off-grid.

Component	Illustrative cost
Low-cost voltage and current measurement hardware	₹1,000–₹3,000
Temperature and environmental sensors	₹500–₹2,500
Microcontroller and communication hardware	₹500–₹1,500
Optional local computing device	₹5,000–₹10,000
Wiring, enclosures, and miscellaneous hardware	₹1,000–₹3,000
Software development	Variable; may be reduced using open-source tools

These estimates exclude the solar panels, inverter, battery, and standard installation costs because the proposed AI layer may be added to an existing solar installation.

For an economical prototype, the system should use an existing computer for model development and a low-cost microcontroller for data collection wherever practical.

The optional computing device may be unnecessary if the selected model can run on existing hardware.

6.1 Cost-Reduction Strategies

The following strategies can reduce implementation costs:

1. Use open-source tools such as Python and suitable machine learning libraries.
2. Start with a small, interpretable model rather than a computationally expensive deep-learning architecture.
3. Reuse compatible sensors and telemetry already present in the inverter.
4. Use local data processing to reduce dependence on paid cloud services.
5. Develop and validate the forecasting model before purchasing additional hardware.
6. Add AI-assisted MPPT only if its measured benefit exceeds the incremental cost.
7. Use modular hardware so that monitoring and forecasting can be implemented before advanced control features.

The economic evaluation must include the cost of model development, installation, maintenance, and replacement, not merely the purchase price of the microcontroller.

7. EXPECTED RESULTS AND DISCUSSION

The following are research hypotheses and expected outcomes, not measured results.

7.1 Improved Monitoring

The proposed system is expected to provide more detailed information about solar power generation, temperature variations, and abnormal operating conditions than a basic monitoring arrangement.
This may help identify problems that would otherwise remain unnoticed until a manual inspection or a substantial loss of generation.

7.2 Better Short-Term Forecasting

The machine learning model is expected to capture relationships between environmental conditions and PV output.
However, the extent of improvement will depend on the quality and quantity of the training data, the local climate, and the selected forecasting horizon.
The model must be tested against simple baselines before any claim of superior accuracy is made.

7.3 Potential Reduction in Maintenance Costs

Early identification of persistent performance deviations may reduce unnecessary inspection visits and help maintenance personnel prioritize genuine problems.
Nevertheless, AI-generated alerts can also produce false alarms. Their economic value depends on whether they improve maintenance decisions sufficiently to offset the cost of monitoring and investigation.

7.4 Improved Energy Utilization

Forecast-informed scheduling may increase the use of solar electricity at the time it is generated.
For systems with batteries, better scheduling may improve battery utilization, provided that the control strategy accounts for conversion losses, battery degradation, and operating constraints.
The benefits will depend on the user's load profile and the local electricity tariff.

7.5 Economic Feasibility

The additional investment in AI is expected to be more attractive when:

- The installation experiences significant avoidable energy losses.
- Maintenance visits are expensive or difficult to arrange.
- Electricity tariffs create a meaningful benefit from improved self-consumption.
- Existing sensors and computing resources can be reused.
- The system operates for enough years to recover the additional investment.

For small installations with reliable conventional controllers and inexpensive maintenance, the cost of AI may exceed the financial benefits.

7.6 Recommended Results Table

After simulation or hardware testing, the following table should be completed using actual measurements.

Evaluation parameter	Conventional system	AI-assisted system
Forecasting MAE	To be measured	To be measured
Forecasting RMSE	To be measured	To be measured
Energy generation (kWh)	To be measured	To be measured
Useful solar energy consumed (kWh)	To be measured	To be measured
Fault-detection recall	Baseline or not applicable	To be measured

False-alarm rate	To be measured, if applicable	To be measured
Annual maintenance cost	To be measured	To be measured
Additional AI investment	Not applicable	To be measured
Annual net economic benefit	Baseline	To be calculated
Payback period	Not applicable	To be calculated

No numerical improvement should be reported until the relevant measurements or validated simulation results are available.

8. CHALLENGES AND LIMITATIONS

8.1 Data Availability

AI models require representative data. Small installations may not have sufficient historical observations to train reliable models.

Public datasets can help during development, but local validation is necessary because environmental conditions and system characteristics vary.

8.2 Sensor Accuracy

Low-cost sensors may introduce measurement errors. Incorrect readings can reduce forecasting accuracy and generate false fault alerts.

Sensor calibration and periodic verification are therefore important.

8.3 Computational Cost

Deep-learning models can require more processing power, memory, and energy than simpler models.

For cost-sensitive installations, lightweight models should be evaluated first.

8.4 Changing Environmental Conditions

A model trained under one set of weather conditions may perform poorly under different seasonal or geographical conditions.

Periodic evaluation and retraining may be necessary.

8.5 Cybersecurity and Privacy

Internet-connected solar systems may be exposed to unauthorized access or data manipulation.

Secure communication, access controls, software updates, and protection of control interfaces are important.

8.6 Safety and Reliability

AI should not replace certified inverter protections, battery management systems, or electrical safety mechanisms.

The system must fail safely if sensor readings are unavailable, communication is interrupted, or the AI model produces invalid output.

8.7 Economic Uncertainty

Energy tariffs, maintenance costs, equipment prices, battery replacement costs, and actual system performance can change over time.

A sensitivity analysis should therefore be performed before claiming that AI makes the overall installation cheaper.

9. FUTURE SCOPE

Further research can extend the proposed framework in several directions.

9.1 Digital Twin Integration

A digital twin can represent the operating condition of a physical solar installation and compare expected performance with actual measurements.
This may support fault investigation, maintenance planning, and evaluation of alternative control strategies.

9.2 Edge AI

Edge AI allows models to operate close to the sensors rather than relying entirely on remote servers.
This can reduce communication requirements and improve operation during internet interruptions.

9.3 Reinforcement Learning

Reinforcement learning may be investigated for optimizing battery charging, flexible load scheduling, and grid interaction.
However, safe operating constraints and realistic electricity tariffs must be included in the evaluation.

9.4 Automated Dust and Shading Detection

Additional sensors or camera-based techniques may help distinguish performance losses caused by shading or soiling from other faults.
The cost of the sensors and the reliability of the diagnosis must be assessed.

9.5 Large-Scale Field Testing

The proposed system should be tested at multiple locations and under different environmental conditions.
Long-term field trials would provide stronger evidence about model reliability, maintenance savings, and economic feasibility.

10. CONCLUSION

Artificial Intelligence has the potential to improve the monitoring, forecasting, maintenance, and energy management of solar photovoltaic systems. However, the use of AI does not automatically guarantee higher energy generation or lower total costs.

This research proposes a modular, cost-effective AI-assisted solar energy framework that combines low-cost sensing hardware, machine learning, anomaly detection, and intelligent energy management.

The design emphasizes the use of existing inverter data, open-source software, lightweight algorithms, and conventional control equipment wherever these provide adequate performance. This approach can reduce unnecessary hardware expenditure while retaining the option to introduce more advanced AI functions when justified by experimental evidence.

The proposed evaluation methodology compares conventional and AI-assisted systems using forecasting accuracy, energy utilization, fault-detection performance, maintenance expenditure, incremental investment, and lifecycle economics.

The central contribution of this work is a practical framework for determining when AI can deliver measurable value in solar energy applications. Actual hardware testing or validated simulation is required to establish the size of any performance improvement and whether the additional investment is economically justified.

In conclusion, **the most cost-effective approach is not necessarily to build the most intelligent solar system, but to implement the simplest AI solution that produces a measurable improvement in performance, reliability, or lifecycle cost.**

REFERENCES

[1] O. Boubaker, "MPPT techniques for photovoltaic systems: a systematic review in current trends and recent advances in artificial intelligence," *Discover Energy*, vol. 3, article 9, 2023. DOI: 10.1007/s43937-023-00024-2.

[2] A. Kumar et al., "Artificial Intelligence Techniques for the Photovoltaic System: A Systematic Review and Analysis for Evaluation and Benchmarking," *Archives of Computational Methods in Engineering*, vol. 31, pp. 4429–4453, 2024. DOI: 10.1007/s11831-024-10125-3.

[3] S. Jadapalli et al., "Scoping review of artificial intelligence approaches for solar energy forecasting addressing methodological developments data practices and operational implications," *Discover Applied Sciences*, vol. 8, article 665, 2026. DOI: 10.1007/s42452-026-08691-1.

[4] K. Y. Yap, C. R. Sarimuthu, and J. M. Y. Lim, "Artificial intelligence based MPPT techniques for solar power system: A review," *Journal of Modern Power Systems and Clean Energy*, vol. 8, no. 6, pp. 1043–1059, 2020. DOI: 10.35833/MPCE.2020.000159.

[5] H. H. Elzohri, K. Sayed, M. Mourad, and A. G. Abo-Khalil, "Advancing solar PV power plants: The role of artificial intelligence in optimization, sustainability, and cost efficiency," *Measurement: Digitalization*, vol. 6, article 100027, 2026. DOI: 10.1016/j.meadig.2026.100027.

[6] A. Hamza et al., "A multi-stage review framework for AI-driven predictive maintenance and fault diagnosis in photovoltaic systems," *Applied Energy*, vol. 393, article 126108, 2025.
DOI: 10.1016/j.apenergy.2025.126108.